

# K-MANO ABSPH MUF ZAPF

Pressure gauge stopcocks, female - male

**HANSA FLEX**

## Īpašības

|                            |                                                                                                 |
|----------------------------|-------------------------------------------------------------------------------------------------|
| <b>Izmantošana</b>         | For all pressure gauges with a flat gasket acc. to DIN 16258                                    |
| <b>Spiediena diapazons</b> | Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures |
| <b>Temperatūra</b>         | Max. +50 °C                                                                                     |
| <b>Korpuss</b>             | Brass with a bare metal surface or stainless steel 1.4571                                       |
| <b>Rokturis</b>            | Plastic                                                                                         |
| <b>Pārbaudes atloks</b>    | -                                                                                               |



## Norāde

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Citi dati pieejami pēc pieprasījuma.

## Apraksts

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Papildu informācija

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Izstrādājums

| Apzīmējums     | Vītnes | PN (bar) | SW (mm) | Materiāls       |
|----------------|--------|----------|---------|-----------------|
| K- 07 20 10 94 | G 1/4  | 6        | 17      | Misiņš          |
| K- 07 20 10 95 | G 3/8  | 16       | 22      | Misiņš          |
| K- 07 20 10 97 | G 1/2  | 25       | 27      | Misiņš          |
| K- 07 20 10 96 | G 1/2  | 25       | 27      | Stainless steel |
| K- 07 20 10 98 | G 1/2  | 25       | 27      | Misiņš          |