

K-MANO ABSPH MUF DREH MUF

Pressure gauge stopcocks, female - loose (rotatable) female

HANSA FLEX

Īpašības

Izmantošana	For all pressure gauges with a flat gasket acc. to DIN 16258
Spiediena diapazons	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Temperatūra	Max. +50 °C
Korpuss	Brass with a bare metal surface or stainless steel 1.4571
Rokturis	Plastic
Pārbaudes atloks	-



Norāde

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Citi dati pieejami pēc pieprasījuma.

Apraksts

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Papildu informācija

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Izstrādājums

Apzīmējums	Vītnes	PN (bar)	SW (mm)	Materiāls
K- 07 20 10 86	G 1/2	25	27	Misiņš
K- 07 20 10 87	G 1/2	25	27	Misiņš