


# K-MANO ABSPH MUF DREH MUF

Pressure gauge stopcocks, female - loose (rotatable) female

**HANSA FLEX**

## Īpašības

<b>Izmantošana</b>	For all pressure gauges with a flat gasket acc. to DIN 16258
<b>Spiediena diapazons</b>	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
<b>Temperatūra</b>	Max. +50 °C
<b>Korpuss</b>	Brass with a bare metal surface or stainless steel 1.4571
<b>Rokturis</b>	Plastic
<b>Pārbaudes atloks</b>	-



## Norāde

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Citi dati pieejami pēc pieprasījuma.

## Apraksts

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Papildu informācija

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Izstrādājums

Apzīmējums	Vītnes	PN (bar)	SW (mm)	Materiāls
K- 07 20 10 86	G 1/2	25	27	Misiņš
K- 07 20 10 87	G 1/2	25	27	Misiņš