

# K-MANO ABSPV ZAPF SPAN MUF 16270A

Pressure gauge valves, male - female/female, DIN 16270

**HANSA FLEX**

## Īpašības

<b>Ekspluatācijas spiediens</b>	max. 250 bar brass, max. 400 bar steel/ stainless steel
<b>Temperatūra</b>	Max. +120 °C with brass/steel; Max. +200 °C for stainless steel
<b>Visu daļu darba vielas</b>	Stainless steel
<b>Blīvēšanas materiāls</b>	PTFE
<b>Korpuss</b>	Brass, black-finished steel or stainless steel 1.4571
<b>Rokrats</b>	Plastic
<b>Spriegošanas uzmevas kupoluzgrieznis</b>	Steel
<b>Vārsta vārpsta, vārsta konuss</b>	Stainless steel



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

## Izstrādājums

Apzīmējums	Vītnes	PN (bar)	SW (mm)	Materiāls
K- 07 20 11 22	G 1/2	250	27	Misiņš
K- 07 20 11 23	G 1/2	400	27	Black-finished steel
K- 07 20 11 21	G 1/2	400	27	Stainless steel