

K-MANO ABSPV ZAPF DREH MUF 16270B

Pressure gauge valves, male - loose female connector and shaft for instrument holder, DIN 16270

HANSA FLEX

Īpašības

| | |
|---|--|
| Ekspluatācijas spiediens | max. 250 bar brass, max. 400 bar steel/ stainless steel |
| Temperatūra | Max. +120 °C with brass/steel; Max. +200 °C for stainless steel |
| Visu daļu darba vielas | Stainless steel |
| Blīvēšanas materiāls | PTFE |
| Korpuss | Brass, black-finished steel or stainless steel 1.4571 |
| Rokrats | Plastic |
| Spriegošanas uzmevas kupoluzgrieznis | Steel |
| Vārsta vārpsta, vārsta konuss | Stainless steel |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

Izstrādājums

| Apzīmējums | Vītnes | PN (bar) | SW (mm) | Materiāls |
|----------------|--------|----------|------------|-----------------|
| K- 07 20 11 16 | G 1/2 | 250 | 27 | Misiņš |
| K- 07 20 11 15 | G 1/2 | 400 | 27 | Stainless steel |