

K-RMM HKR STAHL

Standard pressure gauges with 3-hole bezel, chrome-plated steel, dual scale in bar/psi and clamp fixing, connection on rear

HANSA FLEX

Īpašības

Tips	111.12
Modelis	Bourdon-tube pressure gauge, standard design, mounting ring Chromium plated sheet steel Steel chrome plated or black or with triangular bezel
Izmantošana	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kvalitātes klase	2,5
Vielas temperatūra	maks. +60 °C
Vides temperatūra	no -20 °C līdz +60 °C
Korpuss	Sheet steel
Mērelementa un rādītāja materiāls	Vara sakausējums
Skatstikls	Transparent plastic



Norāde

Citi dati pieejami pēc pieprasījuma.

Izstrādājums

Apzīmējums	Mērīšanas diapazons	Ø (mm)	Savienojums
K- 07 20 04 04	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 05	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 06	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 07	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 08	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 09	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 10	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 11	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 12	0 - 25.0 bar	40,0	G 1/8