

# K-RMM H STAHL

Standard pressure gauges (sheet steel housing / connection on rear, central)

**HANSA FLEX**

## Īpašības

|  |  |
|--|--|
| <b>Tips</b>                              | 111.12   |
| <b>Modelis</b>                           | Bourdon-tube pressure gauge in standard design   |
| <b>Izmantošana</b>                       | gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| <b>Kvalitātes klase</b>                  | 1.6 (Art. No. K-07200599, K-07200600: 2.5)   |
| <b>Vielas temperatūra</b>                | maks. +60 °C   |
| <b>Vides temperatūra</b>                 | no -20 °C līdz +60 °C  |
| <b>Korpuss</b>                           | Sheet steel  |
| <b>Mērelementa un rādītāja materiāls</b> | Vara sakausējums   |
| <b>Skatstikls</b>                        | Transparent plastic  |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Izstrādājums

| Apzīmējums     | Mērīšanas diapazons | Ø (mm) | Savienojums |
|----------------|---------------------|--------|-------------|
| K- 07 20 04 74 | -1 / 0.0 bar        | 40,0   | G 1/8       |
| K- 07 20 04 75 | 0 - 1.6 bar         | 40,0   | G 1/8       |
| K- 07 20 04 76 | 0 - 2.5 bar         | 40,0   | G 1/8       |
| K- 07 20 04 77 | 0 - 4.0 bar         | 40,0   | G 1/8       |
| K- 07 20 04 78 | 0 - 6.0 bar         | 40,0   | G 1/8       |
| K- 07 20 04 79 | 0 - 10.0 bar        | 40,0   | G 1/8       |
| K- 07 20 04 80 | 0 - 16.0 bar        | 40,0   | G 1/8       |
| K- 07 20 04 81 | 0 - 25.0 bar        | 40,0   | G 1/8       |
| K- 07 20 04 82 | 0 - 40.0 bar        | 40,0   | G 1/8       |
| K- 07 20 05 89 | -1 / 0.0 bar        | 50,0   | G 1/4       |
| K- 07 20 05 90 | 0 - 1.0 bar         | 50,0   | G 1/4       |
| K- 07 20 05 91 | 0 - 1.6 bar         | 50,0   | G 1/4       |
| K- 07 20 05 92 | 0 - 2.5 bar         | 50,0   | G 1/4       |
| K- 07 20 05 93 | 0 - 4.0 bar         | 50,0   | G 1/4       |
| K- 07 20 05 94 | 0 - 6.0 bar         | 50,0   | G 1/4       |
| K- 07 20 05 95 | 0 - 10.0 bar        | 50,0   | G 1/4       |
| K- 07 20 05 96 | 0 - 16.0 bar        | 50,0   | G 1/4       |
| K- 07 20 05 97 | 0 - 25.0 bar        | 50,0   | G 1/4       |
| K- 07 20 05 98 | 0 - 40.0 bar        | 50,0   | G 1/4       |
| K- 07 20 05 99 | 0 - 60.0 bar        | 50,0   | G 1/4       |
| K- 07 20 06 00 | 0 - 100.0 bar       | 50,0   | G 1/4       |
| K- 07 20 11 84 | 0 - 1.0 bar         | 40,0   | G 1/8       |