

# K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

**HANSA FLEX**

## Īpašības

Ekspluatācijas temperatūra	-60 °C to +100 °C (PA 12)
Īpašības	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Caurules garums	3 m
Iepakojuma vienība	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Materiāls	Polyamid PA 12, hard (according to DIN 73378)



## Norāde

Operating pressure with 2.5 x overpressure safety!

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

## Izstrādājums

Apzīmējums	Caurules ārējais Ø (mm)	Caurules iekšējais Ø (mm)	maks. ekspluatācijas spiediens pie 20 °C (bar)	Krāsa
K- 07 10 04 57	12	9	38	zils
K- 07 10 04 59	12	9	38	melns
K- 07 10 04 61	15	12	25	zils
K- 07 10 04 63	15	12	25	melns
K- 07 10 04 65	18	14	28	zils
K- 07 10 04 67	18	14	28	melns
K- 07 10 04 69	22	18	22	zils
K- 07 10 04 71	22	18	22	melns
K- 07 10 04 73	28	23	20	zils
K- 07 10 04 75	28	23	20	melns