

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Īpašības

Ekspluatācijas temperatūra	-60 °C to +100 °C (PA 12)
Īpašības	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Caurules garums	3 m
Iepakojuma vienība	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materiāls	Polyamid PA 12, hard (according to DIN 73378)



Norāde

Operating pressure with 2.5 x overpressure safety!

Citi dati pieejami pēc pieprasījuma.

Apraksts

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Izstrādājums

Apzīmējums	Caurules ārējais Ø (mm)	Caurules iekšējais Ø (mm)	maks. ekspluatācijas spiediens pie 20 °C (bar)	Krāsa
K- 07 10 04 56	12	9	38	zils
K- 07 10 04 58	12	9	38	melns
K- 07 10 04 60	15	12	25	zils
K- 07 10 04 62	15	12	25	melns
K- 07 10 04 64	18	14	28	zils
K- 07 10 04 66	18	14	28	melns
K- 07 10 04 68	22	18	22	zils
K- 07 10 04 70	22	18	22	melns
K- 07 10 04 72	28	23	20	zils
K- 07 10 04 74	28	23	20	melns