

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Īpašības

Pieslēguma veids with kink protector, swivel type

Ekspluatācijas temperatūra -40 °C to +74 °C



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Izstrādājums

| Apzīmējums     | Vītnes | Ø šļūtenei iekšpusē<br>(mm) | Ø šļūtenei ārpusē<br>(mm) | Ø ārējam tinumam<br>(mm) | Max. working pressure resistance at<br>23°C<br>(bar) | maks. darba garums<br>(m) |
|----------------|--------|-----------------------------|---------------------------|--------------------------|--|---------------------------|
| K- 07 10 07 43 | G 1/4  | 6,3                         | 9,5                       | 42                       | 14   | 3,0                       |
| K- 07 10 07 44 | G 1/4  | 6,3                         | 9,5                       | 42                       | 14   | 6,0                       |
| K- 07 10 07 45 | G 1/4  | 6,3                         | 9,5                       | 42                       | 14   | 7,5                       |
| K- 07 10 07 46 | G 3/8  | 8,0                         | 12,0                      | 55                       | 14   | 3,0                       |
| K- 07 10 07 47 | G 3/8  | 8,0                         | 12,0                      | 55                       | 14   | 6,0                       |
| K- 07 10 07 48 | G 3/8  | 8,0                         | 12,0                      | 55                       | 14   | 7,5                       |

## Piederumi

K-DREHBARE VERSCHRAUBUNG Swivel adapters