

K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

HANSA FLEX

Īpašības

Korpuss	Amoplast with hinged cover
Iebūvēts korpusā	Hanging eyelets, wall mounting fixing and standing feet
Modelis	Pre-wired
Līniju ievadi	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Aizsardzības veids	IP 44



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Izstrādājums

Apzīmējums	Aprīkojums	Krāsa
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	dzeltens
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	sudrabs

Piederumi

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«