

## Īpašības

<b>Korpuss</b>	Amaplast with hinged cover
<b>Iebūvēts korpusā</b>	Hanging eyelets, wall mounting fixing and standing feet
<b>Drošinātājs</b>	Beneath transparent lid (4 MW)
<b>Modelis</b>	Pre-wired
<b>Līniju ievadi</b>	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection (all openings can be cut out)
<b>Aizsardzības veids</b>	IP 44



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

## Izstrādājums

Apzīmējums	Aprīkojums	Krāsa
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	dzeltens
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	sudrabs

## Piederumi

<b>K-VT 2 KUPPL 7,2 STECKNIP MS</b>	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
<b>K-ZUBEH VSEH 3 KRAFT AIRKRAFT</b>	Accessories for receptacle combinations »3-Kraft« and »airkraft«