

# K-VERSCHLUSSNIPPEL IG MS

Self-sealing plugs, brass

**HANSA FLEX**

## Īpašības

|                                       |   |
|---------------------------------------|---|
| <b>Ekspluatācijas spiediens</b>       | See table. All values referred to a medium temperature of 50 °C (static working pressure)   |
| <b>Gaisa caurplūde</b>                | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| <b>Vielas temperatūra</b>             | -20 °C to +100 °C   |
| <b>Korpuss, uzmava, vārsts</b>        | Brass   |
| <b>Atspere, sprostgredzens, lodes</b> | stain less steel  |
| <b>Blīvēšanas materiāls</b>           | NBR   |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Izstrādājums

| Apzīmējums     | Savienojums  | NW   | Ekspluatācijas spiediens (bar) | Garums (mm) | SW (mm) |
|----------------|--------------|------|--------------------------------|-------------|---------|
| K- 07 40 10 15 | G 1/8 female | 4,3  | 250,0                          | 29,5        | 14      |
| K- 07 40 10 16 | G 1/4 female | 6,3  | 200,0                          | 35,3        | 19      |
| K- 07 40 10 17 | G 3/8 female | 7,5  | 200,0                          | 39,0        | 22      |
| K- 07 40 10 18 | G 1/2 female | 11,0 | 150,0                          | 48,0        | 27      |
| K- 07 40 10 19 | G 3/4 female | 13,0 | 100,0                          | 60,0        | 36      |