


K-VERSCHLUSSNIPPEL IG MS

Self-sealing plugs, brass

HANSA FLEX

Īpašības

| | |
|---------------------------------------|---|
| Ekspluatācijas spiediens | See table. All values referred to a medium temperature of 50 °C (static working pressure) |
| Gaisa caurplūde | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| Vielas temperatūra | -20 °C to +100 °C |
| Korpuss, uzmava, vārsts | Brass |
| Atspere, sprostgredzens, lodes | stain less steel |
| Blīvēšanas materiāls | NBR |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Izstrādājums

| Apzīmējums | Savienojums | NW | Ekspluatācijas spiediens (bar) | Garums (mm) | SW (mm) |
|----------------|--------------|------|--------------------------------|-------------|---------|
| K- 07 40 10 15 | G 1/8 female | 4,3 | 250,0 | 29,5 | 14 |
| K- 07 40 10 16 | G 1/4 female | 6,3 | 200,0 | 35,3 | 19 |
| K- 07 40 10 17 | G 3/8 female | 7,5 | 200,0 | 39,0 | 22 |
| K- 07 40 10 18 | G 1/2 female | 11,0 | 150,0 | 48,0 | 27 |
| K- 07 40 10 19 | G 3/4 female | 13,0 | 100,0 | 60,0 | 36 |