

# K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

**HANSA FLEX**

## Īpašības

|                                       |   |
|---------------------------------------|---|
| <b>Ekspluatācijas spiediens</b>       | See table. All values referred to a medium temperature of 50 °C (static working pressure)   |
| <b>Gaisa caurplūde</b>                | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| <b>Vielas temperatūra</b>             | -20 °C to +90 °C  |
| <b>Korpuss uzmava</b>                 | POM (Delrin), white   |
| <b>Vārsts</b>                         | Stainless steel 1.4305  |
| <b>Atspere, sprostgredzens, lodes</b> | stain less steel  |
| <b>Blīvēšanas materiāls</b>           | NBR   |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Izstrādājums

| Apzīmējums     | Savienojums  | Ekspluatācijas spiediens (bar) | Garums (mm) | NW   | SW (mm) |
|----------------|--------------|--------------------------------|-------------|------|---------|
| K- 07 35 03 76 | G 1/8 female | 15,0                           | 48,5        | 4,3  | 14      |
| K- 07 35 03 77 | G 1/4 female | 15,0                           | 57,6        | 6,0  | 19      |
| K- 07 35 03 78 | G 3/8 female | 15,0                           | 64,2        | 7,5  | 22      |
| K- 07 35 03 79 | G 1/2 female | 10,0                           | 76,0        | 11,0 | 27      |
| K- 07 35 03 80 | G 3/4 female | 10,0                           | 96,0        | 13,0 | 34      |