

K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Gaisa caurplūde	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Vielas temperatūra	-20 °C to +90 °C
Korpuss uzmava	POM (Delrin), white
Vārsts	Stainless steel 1.4305
Atspere, sprostgredzens, lodes	stain less steel
Blīvēšanas materiāls	NBR



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Izstrādājums

Apzīmējums	Savienojums	Ekspluatācijas spiediens (bar)	Garums (mm)	NW	SW (mm)
K- 07 35 03 76	G 1/8 female	15,0	48,5	4,3	14
K- 07 35 03 77	G 1/4 female	15,0	57,6	6,0	19
K- 07 35 03 78	G 3/8 female	15,0	64,2	7,5	22
K- 07 35 03 79	G 1/2 female	10,0	76,0	11,0	27
K- 07 35 03 80	G 3/4 female	10,0	96,0	13,0	34