

K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	0 - 35 bar, maximum static working pressure (non-pulsating)
Gaisa caurplūde	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Vielas temperatūra	-20 °C to +100 °C
Atbloķēšanas uzdevs	Anodised aluminium
Atspere, sprostgredzens, lodes	stain less steel
Bļivēšanas materiāls	NBR



Norāde

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Citi dati pieejami pēc pieprasījuma.

Apraksts

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Izstrādājums

Apzīmējums	Savienojums	Krāsa	Garums (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zaļš	45,0	14
K- 07 35 06 81	G 1/4 male	zaļš	47,0	17
K- 07 35 06 82	G 1/8 female	zaļš	45,0	14
K- 07 35 06 83	G 1/4 female	zaļš	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	zils	45,0	14
K- 07 35 06 89	G 1/4 male	zils	47,0	17
K- 07 35 06 90	G 1/8 female	zils	45,0	14
K- 07 35 06 91	G 1/4 female	zils	47,0	17
K- 07 35 06 92	G 1/8 male	sarkans	45,0	14
K- 07 35 06 93	G 1/4 male	sarkans	47,0	17
K- 07 35 06 94	G 1/8 female	sarkans	45,0	14
K- 07 35 06 95	G 1/4 female	sarkans	47,0	17