


# K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

**HANSA FLEX**

## Īpašības

<b>Ekspluatācijas spiediens</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>Gaisa caurplūde</b>	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Vielas temperatūra</b>	-20 °C to +100 °C
<b>Atbloķēšanas uzdevs</b>	Anodised aluminium
<b>Atspere, sprostgredzens, lodes</b>	stain less steel
<b>Bļīvēšanas materiāls</b>	NBR



## Norāde

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Citi dati pieejami pēc pieprasījuma.

## Apraksts

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Izstrādājums

Apzīmējums	Savienojums	Krāsa	Garums (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zaļš	45,0	14
K- 07 35 06 81	G 1/4 male	zaļš	47,0	17
K- 07 35 06 82	G 1/8 female	zaļš	45,0	14
K- 07 35 06 83	G 1/4 female	zaļš	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	zils	45,0	14
K- 07 35 06 89	G 1/4 male	zils	47,0	17
K- 07 35 06 90	G 1/8 female	zils	45,0	14
K- 07 35 06 91	G 1/4 female	zils	47,0	17
K- 07 35 06 92	G 1/8 male	sarkans	45,0	14
K- 07 35 06 93	G 1/4 male	sarkans	47,0	17
K- 07 35 06 94	G 1/8 female	sarkans	45,0	14
K- 07 35 06 95	G 1/4 female	sarkans	47,0	17