

K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	0 - 35 bar, maximum static working pressure (non-pulsating)
Gaisa caurplūde	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Vielas temperatūra	-20 °C to +100 °C
Korpuss	Brass
Vārsts	Die-cast zinc, nickel-plated
Atbloķēšanas uzmava	Anodised aluminium
Atspere, sprostgredzens, lodes	stain less steel
Bīvēšanas materiāls	NBR



Norāde

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Citi dati pieejami pēc pieprasījuma.

Apraksts

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Izstrādājums

Apzīmējums	Savienojums	Krāsa	Garums (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	zaļš	57,5	19
K- 07 35 08 02	G 3/8 male	zaļš	57,5	19
K- 07 35 08 03	G 1/4 female	zaļš	55,5	19
K- 07 35 08 04	G 3/8 female	zaļš	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	zils	57,5	19
K- 07 35 08 10	G 3/8 male	zils	57,5	19
K- 07 35 08 11	G 1/4 female	zils	55,5	19
K- 07 35 08 12	G 3/8 female	zils	54,5	19
K- 07 35 08 13	G 1/4 male	sarkans	57,5	19
K- 07 35 08 14	G 3/8 male	sarkans	57,5	19
K- 07 35 08 15	G 1/4 female	sarkans	55,5	19
K- 07 35 08 16	G 3/8 female	sarkans	54,5	19