

# K-GRUNDEJEKTION SBP-C ELK

Basic ejector »SBP-C« with blow-off valve and electronic vacuum switch, with integrated silencer

**HANSA FLEX**

## Īpašības

**Īpašības** Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%)  
Connection of compressed air and vacuum with push-in coupling  
Basic housing with connection facility for a vacuum switch  
Maximum suction capacity with minimum compressed air consumption  
Minimum size, low weight  
Various power ratings for optimised air consumption

**Izmantošana** For universal use in handling systems with very high dynamic movements  
Handling all kinds of air-tight components  
For use in separation systems where space is restricted.  
Construction of ejector blocks for centralised or decentralised individual control of suction pads.

**Sprauslu sistēma** Brass

**Savienojums** Push-in coupling

**Trokšņu slāpētājs** Plastic

**Pamatkorpuss** Impact-resistant plastic



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

## Izstrādājums

Apzīmējums	Sprauslu izmērs	Iesūkšanas vārsts miera stāvoklī	Saspiegtā gaisa pieslēgums	Vakuuma pieslēgums	Izmērs
K- 07 45 01 20	1,0	NO	6 mm	8 mm	142mm x 15mm x 50mm
K- 07 45 01 22	1,5	NO	6 mm	8 mm	142mm x 15mm x 50mm
K- 07 45 01 24	2,0	NO	8 mm	10 mm	228mm x 20mm x 72mm
K- 07 45 01 26	2,5	NO	8 mm	10 mm	228mm x 20mm x 72mm

## Piederumi

K-ERSATZSCHALLDAEMPFER 1	Replacement silencers
K-GRUNDPLATTEN 1	Base plate
K-BEFESTIGUNGSSAETZE 1	Mounting kit