K-FEDERSTOESSEL
Spring plungers

Īpašības

Izmantošana	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatūra min.	0 °C
Temperatūra max.	80 °C
Sūcēja pieslēgums	M 3 female
Modelis	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Amortizācijas gājiens	5,0 mm



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Suitable for all round or oval suction pads in our standard range.

Izstrādājums

Apzīmējums	Vakuuma pieslēgums	Garums (mm)	Vertikālā noslodze (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400

Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.