

# K-FEDERSTOESSEL

Spring plungers

**HANSA FLEX**

## Īpašības

<b>Izmantošana</b>	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
<b>Temperatūra min.</b>	0 °C
<b>Temperatūra max.</b>	80 °C
<b>Sūcēja pieslēgums</b>	M 3 female
<b>Modelis</b>	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
<b>Amortizācijas gājiens</b>	5,0 mm



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Suitable for all round or oval suction pads in our standard range.

## Izstrādājums

Apzīmējums	Vakuuma pieslēgums	Garums (mm)	Vertikālā noslodze (N/m <sup>2</sup> )
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400