

# K-DRUCKSCHALTER VAKUUM

Combined vacuum/pressure switch

**HANSA FLEX**

## Īpašības

|                               |   |
|-------------------------------|---|
| Modelis                       | PNP                                     |
| Mērīšanas vielas pieslēgums   | G 1/8 male and M 5 female               |
| Histerēze                     | Adjustable: 3 to 25% of set value       |
| Temperatūras diapazons        | 0 - 50 °C                               |
| Darba vides                   | Non-aggressive gases. dry, oil-free air |
| Korpuss                       | Polycarbonate                           |
| Izejas signāls                | Analogue: 1 to 5 V                      |
| Elektriskais pieslēgums       | Male connector M8, four pin             |
| Slēgšanas daudzums            | 125 mA                                  |
| Strāvas patēriņš              | 30 mA                                   |
| Aizdedzes stāvokļa indikators | LED                                     |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Universal electronic vacuum and pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly at the point of use. <br>Suitable for all special applications in the vacuum and compressed air sectors. Adjustable vacuum limit value and continuous vacuum monitoring.

## Izstrādājums

| Apzīmējums     | G1 ārpusē | G2 iekšpusē | G3 ārpusē | L<br>(mm) | L1<br>(mm) | Mērīšanas diapazons | Sriegums       |
|----------------|-----------|-------------|-----------|-----------|------------|---------------------|----------------|
| K- 07 45 01 31 | G 1/8     | M 5         | M 8 x 1   | 44,0      | 62,0       | -1 bis +10 bar      | 10.8 - 30 V DC |