

# K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

**HANSA FLEX**

## Īpašības

Vielas temperatūra	-5 °C to +80 °C
maks. izslēgšanas spiediens	16 bar
Slēgšanas daudzums	5,5 kW
Kontaktu veids	NC (3-pole)
maks. slēgšanas biežums	120 (electrical), 600 (mechanical)
Aizsardzības veids	IP 54



## Norāde

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Citi dati pieejami pēc pieprasījuma.

## Apraksts

Three-phase version

## Pasūtījuma norādes

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Papildu informācija

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Izstrādājums

Apzīmējums	Saspiestā gaisa pieslēgums	Iestatīšanas diapazons
K- 07 30 24 24	G 1/2	2,0 - 11,0 bar
K- 07 30 24 26	G 1/2	2,5 - 16,0 bar