

K-DRS STANDARD

Standard pressure switches

HANSA FLEX

Īpašības

Modelis	Spring-loaded diaphragm (NBR); Spring-loaded piston; (10 to 70 bar versions)
Izmantošana	Air, hydraulic oil, oil emulsions, water
Vides temperatūra	-25 °C to +85 °C
Elektriskais pieslēgums	Tab connectors 2 x 6.3 x 0.8
Slēgšanas biežums	200/min.
Slēgšanas spriegums	42 V
Materiāls	Galvanised steel



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Izstrādājums

Apzīmējums	Vītnes	Iestatīšanas diapazons	Funkcija
K- 07 30 24 94	G 1/8	0,3 - 2,0 bar	closer
K- 07 30 24 95	G 1/8	1,0 - 10,0 bar	closer
K- 07 30 24 96	G 1/8	10,0 - 70,0 bar	closer
K- 07 30 24 97	G 1/4	0,3 - 2,0 bar	closer
K- 07 30 24 98	G 1/4	1,0 - 10,0 bar	closer
K- 07 30 24 99	G 1/4	10,0 - 70,0 bar	closer
K- 07 30 24 10	G 1/8	0,3 - 2,0 bar	opener
K- 07 30 24 11	G 1/8	1,0 - 10,0 bar	opener
K- 07 30 24 12	G 1/8	10,0 - 70,0 bar	opener
K- 07 30 24 13	G 1/4	0,3 - 2,0 bar	opener
K- 07 30 24 14	G 1/4	1,0 - 10,0 bar	opener
K- 07 30 24 15	G 1/4	10,0 - 70,0 bar	opener