

# K-DRS W WECHSELKONTAKT ANFLANSCHB<sup>AD</sup>

Pressure switches changeover type, flange mounting

**HANSA FLEX**

## Īpašības

<b>Modelis</b>	Spring-loaded diaphragm (NBR)
<b>Izmantošana</b>	Air, neutral gases (lubricated or unlubricated)
<b>Vides temperatūra</b>	-25 °C to +85 °C
<b>Elektriskais pieslēgums</b>	Coupling plug PG 11 P nach ISO 4400
<b>Slēgšanas biežums</b>	60/min.
<b>Slēgšanas spriegums</b>	max. 250 V AC/DC
<b>Funkcija</b>	Changeover
<b>Materiāls</b>	to 10 bar: plastic Grivory (PA 61/XT) bzw.; to 16 bar: Alu black eloxed



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Izstrādājums

Apzīmējums	Vītnes	Iestatīšanas diapazons
K- 07 30 28 42	G 1/4	0,2 - 6,0 bar
K- 07 30 28 43	G 1/4	0,5 - 10,0 bar
K- 07 30 28 44	G 1/4	0,5 - 16,0 bar