

# K-DRS W WECHSELKONTAKT ANFLANSCHB<sup>AD</sup>

Pressure switches changeover type, flange mounting

**HANSA FLEX**

## Īpašības

|                                |   |
|--------------------------------|---|
| <b>Modelis</b>                 | Spring-loaded diaphragm (NBR)   |
| <b>Izmantošana</b>             | Air, neutral gases (lubricated or unlubricated)                         |
| <b>Vides temperatūra</b>       | -25 °C to +85 °C  |
| <b>Elektriskais pieslēgums</b> | Coupling plug PG 11 P nach ISO 4400                                     |
| <b>Slēgšanas biežums</b>       | 60/min.   |
| <b>Slēgšanas spriegums</b>     | max. 250 V AC/DC  |
| <b>Funkcija</b>                | Changeover  |
| <b>Materiāls</b>               | to 10 bar: plastic Grivory (PA 61/XT) bzw.; to 16 bar: Alu black eloxed |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

## Izstrādājums

| Apzīmējums     | Vītnes | Iestatīšanas diapazons |
|----------------|--------|------------------------|
| K- 07 30 28 42 | G 1/4  | 0,2 - 6,0 bar          |
| K- 07 30 28 43 | G 1/4  | 0,5 - 10,0 bar         |
| K- 07 30 28 44 | G 1/4  | 0,5 - 16,0 bar         |