



K-S-BKR M ENTL

Safety ball valves

HANSA FLEX

Īpašības

Ekspluatācijas temperatūra	0 °C to +60 °C
Vītnes apraksts	Rp thread acc. to ISO 7-1
Bļivēšanas materiāls	PTFE
Korpuss, lode, vārpsta, bļivslēgš	Nickel-plated brass
Svira	Die-cast aluminium, black
Materiāls	sealing: PTFE



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

2/2-way brass safety ball valves. Specially designed for pneumatic applications. The ball valve shuts off the supply side and relieves the application into the atmosphere.

Izstrādājums

Apzīmējums	DN	Vītnes	A (mm)	B (mm)	L (mm)	maks. ekspluatācijas spiediens pie 20 °C (bar)
K- 07 30 21 08	8	Rp 1/4	100,0	61,0	52,0	12
K- 07 30 21 09	10	Rp 3/8	100,0	61,0	55,0	12
K- 07 30 21 10	15	Rp 1/2	100,0	64,0	69,0	12
K- 07 30 21 11	20	Rp 3/4	120,0	76,0	77,0	12
K- 07 30 21 12	25	Rp 1	120,0	80,0	89,0	12
K- 07 30 21 13	32	Rp 1 1/4	150,0	98,0	103,0	12
K- 07 30 21 14	40	Rp 1 1/2	150,0	104,0	114,0	12
K- 07 30 21 15	50	Rp 2	175,0	119,0	134,0	12