

# K-ABBLV 2

Blow-off safety valves G 1/4

**HANSA FLEX**

## Īpašības

|                            |              |
|----------------------------|--------------|
| Ekspluatācijas spiediens   | 0.5 - 60 bar |
| Ekspluatācijas temperatūra | max. 180 °C  |
| Blīvējumi                  | FKM          |
| Korpuss                    | Brass        |



## Norāde

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Manual adjustment of the blow-off pressure (lock nut).

## Pasūtījuma norādes

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Papildu informācija

These blow-off valves can also be supplied with a fixed setting and a TÜV type test number. Please ask for an offer.

## Izstrādājums

| Apzīmējums     | Vītnes | Sākuma spiediens | Izpūtes jauda | C<br>(mm) | D<br>(mm) | do<br>(mm) | SW<br>(mm) |
|----------------|--------|------------------|---------------|-----------|-----------|------------|------------|
| K- 07 30 29 18 | G 1/4  | 0.5 - 1.0 bar    | to 50 l/min   | 27,0      | 7,0       | 3,0        | 16         |
| K- 07 30 21 95 | G 1/4  | 1.0 - 4.0 bar    | to 200 l/min  | 27,0      | 7,0       | 3,0        | 16         |
| K- 07 30 21 96 | G 1/4  | 3.0 - 7.0 bar    | to 350 l/min  | 27,0      | 7,0       | 3,0        | 16         |
| K- 07 30 21 97 | G 1/4  | 6.0 - 12.0 bar   | to 650 l/min  | 27,0      | 7,0       | 3,0        | 16         |
| K- 07 30 21 98 | G 1/4  | 10.0 - 18.0 bar  | to 870 l/min  | 27,0      | 7,0       | 3,0        | 16         |
| K- 07 30 21 99 | G 1/4  | 16.0 - 32.0 bar  | to 1600 l/min | 27,0      | 7,0       | 3,0        | 16         |
| K- 07 30 22 00 | G 1/4  | 30.0 - 60.0 bar  | to 3000 l/min | 27,0      | 7,0       | 3,0        | 16         |