


# K-SCHLAUCH VB

Hose connectors

**HANSA FLEX**

## Īpašības

|                                 |   |
|---------------------------------|---|
| <b>Ekspluatācijas spiediens</b> | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 1 bar (at 60 °C) |
| <b>Skrūvelements</b>            | Polyamide (PA)  |
| <b>Spīlgredzens</b>             | Polypropylene (PP)  |
| <b>Uzgrieznis</b>               | Polypropylene (PP)  |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. <br>Not suitable for use with acids.

## Izstrādājums

| Apzīmējums     | šūtenei      | L1<br>(mm) | SW    |
|----------------|--------------|------------|-------|
| K- 07 40 32 62 | 4 mm / 6 mm  | 39,0       | 14 mm |
| K- 07 40 32 63 | 6 mm / 8 mm  | 49,0       | 19 mm |
| K- 07 40 32 64 | 8 mm / 10 mm | 55,0       | 22 mm |
| K- 07 40 32 65 | 9 mm / 12 mm | 64,0       | 24 mm |