


# K-GAM IG 4

Female connectors, female thread

**HANSA FLEX**

## Īpašības

|                                |                 |
|--------------------------------|-----------------|
| maks. ekspluatācijas spiediens | 18 bar          |
| izmantojamās šļūtenes          | PA, PE, PU      |
| Materiāls                      | Niķelēts misiņš |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Izstrādājums

| Apzīmējums     | Vītnes | šļūtenei     | L1<br>(mm) | SW    |
|----------------|--------|--------------|------------|-------|
| K- 07 40 33 77 | G 1/8  | 6 mm / 4 mm  | 25,0       | 14 mm |
| K- 07 40 33 78 | G 1/8  | 8 mm / 6 mm  | 25,0       | 14 mm |
| K- 07 40 33 75 | G 1/4  | 6 mm / 4 mm  | 29,0       | 17 mm |
| K- 07 40 33 76 | G 1/4  | 8 mm / 6 mm  | 29,0       | 17 mm |
| K- 07 40 33 74 | G 1/4  | 10 mm / 8 mm | 30,5       | 17 mm |
| K- 07 40 33 73 | G 1/2  | 8 mm / 6 mm  | 33,0       | 24 mm |
| K- 07 40 33 72 | G 1/2  | 10 mm / 8 mm | 34,5       | 24 mm |
| K- 07 40 33 80 | G 3/8  | 6 mm / 4 mm  | 29,5       | 20 mm |
| K- 07 40 33 81 | G 3/8  | 8 mm / 6 mm  | 29,5       | 20 mm |
| K- 07 40 33 79 | G 3/8  | 10 mm / 8 mm | 31,0       | 20 mm |