


# K-KONDENSA DRUKODRAIN PLUS

Drain for compressed air condensate

**HANSA FLEX**

## Īpašības

Filtra pieslēguma jauda	100 m <sup>3</sup> /min
Kompresora pieslēguma jauda	10 m <sup>3</sup> /min
Žvētāja pieslēguma jauda	20 m <sup>3</sup> /min



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Compact and exceptionally reliable, level-controlled drain for compressed air condensate. The condensate enters the integrated collecting tank, in which the level is continuously monitored. When the condensate reaches the maximum mark, the pilot valve opens and the condensate is forced into the discharge line by the system pressure. The valve closes again when the level reaches the minimum mark. Benefits of »drukodrain plus«: No pressure loss, Diaphragm protected by integrated cup filter, Test button for manual outlet, Auto-reset function, Suitable for all condensate types.

## Pasūtījuma norādes

The following voltages on request: 24 VDC, 24 VAC DC, 24 VAC / 50 Hz, 110 VAC / 50 Hz, 115 V / 50 Hz

## Izstrādājums

Apzīmējums	Ekspluatācijas spiediens bar	Spriegums
K- 07 25 09 24	0.2 - 16 bar	230 VAC / 50 Hz