
K-PROP REGELVE SENTRONIC D

Proportional control valves, digital, 24 VDC



Īpašības	
Vielas temperatūra	0 - 60 °C
Vides temperatūra	0 - 50 °C
Darba vides	Air or neutral gases (≤ 50 µm filter specified)
Spiediena diapazons	0 - 10 bar
Vadība	0 to 10 V (on request: 0 to 20 mA or 4 to 20 mA)
Vēlamā vērtība elektriski	0 - 10 V
Analogā izeja	0 - 10 V
Darbība	Proportional solenoid valve
Digitālā izeja	Pressure switch output PNP +/- 5%
Drošinātāja pozīcija	Pressure relieved in case of loss of voltage
lekšējās daļas	POM
Blīvēšanas materiāls	NBR
Korpuss	Aluminium





Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital. https://document.com/stepless-adjustment of these parameters is vital. https://document.com/stepless-adjustment of these parameters is vital. https://document.com/stepless-adjustment-of-these parameters is vital. https://document.com/steples

Izstrād	āi	ums
ızsırau	aı	ullio

Apzīmējums	Savienojums	DN	Caurplūde (L/min)	В	C (mm)
K- 07 25 10 04	G 1/8	4	780	52,0 mm	112,0
K- 07 25 10 05	G 1/4	4	780	52,0 mm	112,0
K- 07 25 10 06	G 1/4	8	1750	66,0 mm	138,0
K- 07 25 10 07	G 3/8	8	1750	66,0 mm	138,0