

# K-FLASCHENDRUCKR 300 N GASE

Pudeles spiediena regulators, pudeles spiediens 300 bar, nedegošām gāzēm

**HANSA FLEX**

## Īpašības

<b>Satura manometrs</b>	0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene
<b>Materiāls</b>	Presētais misiņš
<b>Pudeles pieslēgums</b>	W 30 x 2



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

## Izstrādājums

Apzīmējums	Gāzes veids	Ekspluatācijas spiediens bar
K- 07 25 07 22	Oxygen	0 - 10,0 bar
K- 07 25 07 23	Compressed air	0 - 10,0 bar
K- 07 25 07 24	Nitrogen	0 - 10,0 bar
K- 07 25 07 25	Nitrogen	0 - 20,0 bar

## Rezerves daļas

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	Aizsargvāciņi