

K-3/2-BKR HANSA

Ball valves

HANSA FLEX

Īpašības

| | |
|------------------------------|---|
| ļeejas spiediens | 0 - 16 bar |
| Temperatūras diapazons | -10 °C to +50 °C |
| Darba vides | Saspiests gaiss |
| Pieslēguma vītne | Material: Die-cast zinc |
| Korpuss | Material: Grivory® (PA 66) |
| Caurplūdes vērtības mērījums | At P2 = 6 bar, pressure drop $\Delta p = 1$ bar |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Closable ball valve in 3/2-way design, mechanically actuated. Toggle 90° rotatable and with switch position indicator: Traverse: Inlet port blocked - outlet port exhausted

Longitudinal: Inlet port and outlet port connected - exhaust blocked. Exhaust air can be collected.

Papildu informācija

The price does not include a padlock. Please order separately.

Izstrādājums

| Apzīmējums | Vītne | Izeja | Caurplūde (L/min) | A (mm) | B | C (mm) |
|----------------|-------|-------|-------------------|--------|----------|--------|
| K- 07 25 11 23 | G 1/4 | 1/4 | 1900 | 52,0 | 87,5 mm | 54,5 |
| K- 07 25 11 24 | G 3/8 | 1/4 | 1900 | 52,0 | 87,5 mm | 54,5 |
| K- 07 25 11 43 | G 3/8 | 1/2 | 11000 | 63,0 | 127,0 mm | 70,5 |
| K- 07 25 11 44 | G 1/2 | 1/2 | 11000 | 63,0 | 127,0 mm | 70,5 |
| K- 07 25 11 45 | G 3/4 | 3/4 | 25000 | 85,0 | 144,7 mm | 93,7 |
| K- 07 25 11 46 | G 1 | 3/4 | 25000 | 85,0 | 144,7 mm | 93,7 |

Piederumi

K-VORHAENGESCHLOSS Padlock

Rezerves daļas

K-HALTERBAUSATZ HANSA Holder HANSA