



K-FILTER INLINE

Filters

HANSA FLEX

Īpašības

| | |
|------------------------|---------------------|
| ļeejas spiediens | Max. 18 bar |
| Temperatūras diapazons | 0 °C to +80 °C |
| Filtra smalkums | 36,00 µm |
| Filtrs | Nickel-plated brass |
| Korpuss | Brass |
| citas daļas | NBR |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

For integration in a pneumatic system if different system
sections or tools require different air qualities.

Izstrādājums

| Apzīmējums | Vītnes | A (mm) | L (mm) | SW (mm) |
|----------------|-----------------------|-----------|-----------|------------|
| K- 07 25 05 72 | G 1/8 female/female | 16,0 | 36,0 | 17 |
| K- 07 25 05 73 | G 1/4 female/female | 18,0 | 41,0 | 19 |
| K- 07 25 05 74 | G 3/8 female / female | 22,0 | 53,0 | 24 |
| K- 07 25 05 75 | G 1/2 female/female | 28,4 | 62,0 | 30 |
| K- 07 25 05 76 | G 1/8 female/male | 16,0 | 36,0 | 17 |
| K- 07 25 05 77 | G 1/4 female/male | 18,0 | 41,0 | 19 |
| K- 07 25 05 78 | G 3/8 female / male | 22,0 | 53,0 | 24 |
| K- 07 25 05 79 | G 1/2 female/male | 28,4 | 62,0 | 30 |