

# K-WTEH 3-TLG PC-BEHAEL MULTIFIX

Service units, 3-piece with polycarbonate bowl

**HANSA FLEX**

## Īpašības

|                               |  |
|-------------------------------|--|
| ļeejas spiediens              | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)     |
| Vielas temperatūra            | max. 60 °C   |
| Vides temperatūra             | Max. 60 °C   |
| Poru attālums filtra elementā | 5 µm (BG 1 / BG 2), 40 µm (BG 3)                               |
| Blīvēšanas materiāls          | NBR  |
| Atsperes korpus               | POM-brass  |
| Korpuss                       | Die-cast zinc, Aluminium for G 1 variant                       |
| Pilienu aizsargs              | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)           |
| Drain valve                   | Semi-automatic   |
| Caurplūdes vērtības mērījums  | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

## Pasūtījuma norādes

3-piece service units are also available in other control ranges (0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

## Papildu informācija

1500 l/min: P1: 10 bar, P2: 7 bar,  $\Delta p \leq 0.1$  bar.

## Izstrādājums

| Apzīmējums     | Vītnes | Regulēšanas diapazons | Caurplūde (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Tipizmērs |
|----------------|--------|-----------------------|-------------------|--------|----------|--------|--------|----|-----------|
| K- 07 25 01 10 | G 1/4  | 0.5 - 10 bar          | 1100              | 137,8  | 192,1 mm | 67,0   | 125,1  | 6  | 1         |
| K- 07 25 01 13 | G 3/8  | 0.5 - 10 bar          | 1100              | 137,8  | 192,1 mm | 67,0   | 125,1  | 10 | 1         |
| K- 07 25 01 16 | G 1/2  | 0.5 - 10 bar          | 3000              | 200,8  | 246,3 mm | 99,0   | 147,3  | 15 | 2         |
| K- 07 25 01 19 | G 3/4  | 0.5 - 10 bar          | 3000              | 200,8  | 246,3 mm | 99,0   | 147,3  | 25 | 2         |
| K- 07 25 01 22 | G 1    | 0.5 - 10 bar          | 11300             | 300,0  | 381,8 mm | 128,0  | 253,8  | 25 | 3         |

## Rezerves daļas

|                                  |                               |
|----------------------------------|-------------------------------|
| K-HALTERBAUSATZ                  | Holder                        |
| K-SCHALTAFELMUTTER               | Nut                           |
| K-HALTERBAUSATZ MULTIFIX         | Holder                        |
| K-KOPPELPAKET MEHR               | Coupling packet               |
| K-KOPPELPAKET SCHMA              | Coupling packet               |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler              |
| K-PC-BEHAELTER FILTER MULTIFIX   | Polycarbonate tank filter     |
| K-SCHUTZKORB G                   | Protective cage               |
| K-TROPFAUFSATZ POLYCARBO 1       | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL            | Drip attachment metal         |
| K-FILTERELEMENT                  | Filter element                |
| K-AUTOMAT ABLASSVENTIL           | Automatic drain valve         |
| K-VERSCHLEI-SATZ                 | Set of wearing parts          |