

# K-HS RD

Unidirectional banjo valves, pneumatic release, port 2 with female thread

**HANSA FLEX**

## Īpašības

|                        |  |
|------------------------|--|
| Darba spiediens        | 0.3 - 10 bar   |
| Regulēšanas spiediens  | 0.5 - 2.5 bar, depending on operating pressure                       |
| Vielas temperatūra     | max. 60 °C   |
| Uzstādīšanas stāvoklis | Any. The ring piece must be positioned before the valve is tightened |
| Materiāls              | Niķelēts misiņš  |
| Blīvēšanas materiāls   | Perbunan   |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections.

## Izstrādājums

| Apzīmējums     | Port 1 | Port 2 | Savienojums 3 | B<br>(mm) | C<br>(mm) |
|----------------|--------|--------|---------------|-----------|-----------|
| K- 07 15 07 04 | G 1/8  | G 1/8  | M 5           | 38,0      | 21,5      |
| K- 07 15 07 03 | G 1/4  | G 1/4  | G 1/8         | 43,0      | 25,4      |
| K- 07 15 07 05 | G 3/8  | G 3/8  | G 1/8         | 46,0      | 31,6      |
| K- 07 15 07 02 | G 1/2  | G 1/2  | G 1/8         | 52,0      | 32,0      |