

# K-PNEU LOGIKELEMENTE

Pneumatic logic elements

**HANSA FLEX**

## Īpašības

<b>Darba spiediens</b>	OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
<b>Temperatūras diapazons</b>	-10 °C to +60 °C
<b>Savienojums</b>	Push-in fitting for 4 mm pipe
<b>Caurplūdes daudzums</b>	100 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Nominālais <math>\varnothing</math></b>	2,7 mm
<b>Atiestatīšana</b>	OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
<b>Materiāls</b>	Technopolymer
<b>Aizbīdnis</b>	Aluminium
<b>Bīvēšanas materiāls</b>	NBR



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the  $\Omega$ -rail (DIN EN 50022) integral with the body.

## Izstrādājums

Apzīmējums	Funkcija	Augstums (mm)	Garums (mm)
K- 07 15 13 77	OR	40	38,5
K- 07 15 13 78	AND	40	38,5
K- 07 15 13 79	NOT	40	55,2
K- 07 15 13 80	YES	40	55,2
K- 07 15 13 81	MEMORY	41	89,5