

K-WV 5/2 ELEKTROPNEUMATISCH

5/2-way pilot valves

HANSA FLEX

Īpašības

| | |
|----------------------------------|--|
| Ekspluatācijas spiediens | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\ninvacuum up to 10 bar (external pilot air) |
| min. darba spiediens | 2.5 bar (monostable), 1.0 bar (bistable) |
| Temperatūras diapazons | -10 °C to +60 °C |
| Caurplūde 6 bar un 10 bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Caurplūde 6 bar un 5 bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |



Norāde

Citi dati pieejami pēc pieprasījuma.

Izstrādājums

| Apzīmējums | Savienojums | Spriegums | DN | Funkcija | Slēguma shēmas numurs | Vadība |
|----------------|-------------|--------------|----|----------|-----------------------|--------|
| K- 07 15 01 93 | G 1/8 | 24 V DC | 5 | 5/2-way | 35 | |
| K- 07 15 01 94 | G 1/4 | 24 V DC | 8 | 5/2-way | 35 | |
| K- 07 15 25 81 | G 3/8 | 24 V DC | 13 | 5/2-way | 35 | |
| K- 07 15 01 95 | G 1/2" | 24 V DC | 15 | 5/2-way | 35 | |
| K- 07 15 01 96 | G 1/8 | 230 V, 50 Hz | 5 | 5/2-way | 35 | |
| K- 07 15 01 97 | G 1/4 | 230 V, 50 Hz | 8 | 5/2-way | 35 | |
| K- 07 15 25 82 | G 3/8 | 230 V, 50 Hz | 13 | 5/2-way | 35 | |
| K- 07 15 01 98 | G 1/2" | 230 V, 50 Hz | 15 | 5/2-way | 35 | |
| K- 07 15 01 99 | G 1/8 | 24 V DC | 5 | 5/2-way | 36 | |
| K- 07 15 02 00 | G 1/4 | 24 V DC | 8 | 5/2-way | 36 | |
| K- 07 15 25 83 | G 3/8 | 24 V DC | 13 | 5/2-way | 36 | |
| K- 07 15 02 01 | G 1/2" | 24 V DC | 15 | 5/2-way | 36 | |
| K- 07 15 02 02 | G 1/8 | 230 V, 50 Hz | 5 | 5/2-way | 36 | |
| K- 07 15 02 03 | G 1/4 | 230 V, 50 Hz | 8 | 5/2-way | 36 | |
| K- 07 15 25 84 | G 3/8 | 230 V, 50 Hz | 13 | 5/2-way | 36 | |
| K- 07 15 02 04 | G 1/2" | 230 V, 50 Hz | 15 | 5/2-way | 36 | |