

K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
Temperatūras diapazons	-10 °C to +60 °C
Caurplūde 6 bar un 10 bar	550 NI/min
Caurplūde 6 bar un 5 bar	400 NI/min
Vārsta korpuss	Alumīnijs
Atspere	Special steel
Virzulis	Aluminium
Bīvēšanas materiāls	NBR



Norāde

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.

Citi dati pieejami pēc pieprasījuma.

Papildu informācija

Important: The scope of supply does not include a connector. Please order separately.

Izstrādājums

Apzīmējums	Savienojums	Simbols	Darbība	Slēguma stāvokļi
K- 07 15 00 82	G 1/8	9	monostable	2
K- 07 15 00 83	G 1/8	10	bistabils	2
K- 07 15 00 84	G 1/8	11	monostable	3*
K- 07 15 00 85	G 1/8	12	bistabils	3*