# K-SPIR SCHL KUPPL SET SVKM

Spiral hose and coupling kits, with quick disconnect couplings DN 7.6

## Īpašības

| | |
|---|---|
| **Ekspluatācijas spiediens** | 10 bar |
| **Vielas temperatūra** | -20 °C to +60 °C |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Izstrādājums

| Apzīmējums | Šļūtenes izmērs | Ø spirālei (mm) | Darba garums (m) |
|---|---|---|---|
| **K- 07 10 07 59** | 10 mm x 6,5 mm | 52 | 4,0 |
| **K- 07 10 07 60** | 10 mm x 6,5 mm | 52 | 6,0 |
| **K- 07 10 07 61** | 10 mm x 6,5 mm | 52 | 8,0 |
| **K- 07 10 07 62** | 12 mm x 8 mm | 65 | 4,0 |
| **K- 07 10 07 63** | 12 mm x 8 mm | 65 | 6,0 |
| **K- 07 10 07 64** | 12 mm x 8 mm | 65 | 8,0 |

*Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.*