


# K-VT 2 ABGAENGE G

Manifolds

**HANSA FLEX**

## Īpašības

|                     |                        |
|---------------------|------------------------|
| ļeejas spiediens    | 0 - 9 bar              |
| Vielas temperatūra  | max. 70 °C             |
| Vides temperatūra   | Max. 70 °C             |
| Bīvēšanas materiāls | NBR                    |
| Korpuss             | Die-cast aluminium     |
| Papildu dati        | User manual on request |



## Izstrādājums

| Apzīmējums     | Vītnes | A<br>(mm) | B       | C<br>(mm) | D<br>(mm) | Tipizmērs |
|----------------|--------|-----------|---------|-----------|-----------|-----------|
| K- 07 25 12 19 | G 1/4  | 35,0      | 44,0 mm | 22,0      | 22,0      | 200       |
| K- 07 25 12 20 | G 3/8  | 35,0      | 44,0 mm | 22,0      | 22,0      | 200       |
| K- 07 25 12 21 | G 3/8  | 42,0      | 52,0 mm | 26,0      | 26,0      | 300       |
| K- 07 25 12 22 | G 1/2  | 42,0      | 52,0 mm | 26,0      | 26,0      | 300       |
| K- 07 25 12 23 | G 3/4  | 60,0      | 76,0 mm | 38,0      | 38,0      | 600       |
| K- 07 25 12 24 | G 1    | 60,0      | 76,0 mm | 38,0      | 38,0      | 600       |

## Piederumi

|                      |                 |
|----------------------|-----------------|
| K-VERBINDUNGELEMENTE | Connecting sets |
| K-WANDHALTER         | Wall bracket    |