

K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

HANSA FLEX

Īpašības

| | |
|------------------------------|--------------------------------|
| Ekspluatācijas spiediens | Max. 15 bar |
| Stiprinājuma griezes moments | 4 Nm |
| MS vītnes griezes moments | 12 Nm |
| Temperatūras diapazons | -10 °C to +50 °C |
| Korpuss | Glass fibre-reinforced plastic |
| Vītne | Brass |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Izstrādājums

| Apzīmējums | Ieejas vītnes | Savienojošās vītnes |
|----------------|---------------|---------------------|
| K- 07 40 48 12 | G 1/2" | 1 x G 1/2 |
| K- 07 40 48 13 | G 1/2" | 2 x G 1/2 |
| K- 07 40 48 14 | G 1/2" | 3 x G 1/2 |
| K- 07 40 48 15 | G 3/4" | 1 x G 1/2 |
| K- 07 40 48 16 | G 3/4" | 2 x G 1/2 |
| K- 07 40 48 17 | G 3/4" | 3 x G 1/2 |