

K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

HANSA FLEX

Īpašības

Modelis	Calibration, testing and service unit
Precizitāte	0,25% FS
Mērīšanas vietas temperatūra	-20 °C to +80 °C
Vides temperatūra	-10 °C to +50 °C
Daļas, kas saskaras ar mērīšanas vielu	CrNi-steel with NBR seal
Korpuss	Die-cast zinc



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

Papildu informācija

Further measuring ranges on request

Izstrādājums

Apzīmējums	Mērīšanas diapazons	Savienojums
K- 07 20 12 70	-0.95 / +40 bar	G 1/4