

K-DRS WECHSELKONTAK ANFLANSCHBAR DS

Pressure switches, changeover type, suitable for flange mounting
K-07302861

HANSA FLEX

Īpašības

Modelis	Spring-loaded diaphragm (NBR)
Izmantošana	Air, neutral gases (lubricated or unlubricated)
Vides temperatūra	-10 °C to +60 °C
Elektriskais pieslēgums	Pg 11P coupling plug, acc. to ISO 4400
Slēgšanas biežums	60/min.
Slēgšanas spriegums	max. 250 V AC/DC
Funkcija	Changeover
Aizsardzības veids	IP 65
Materiāls	Plastic Grivory (PA 61/XT)



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Special pressure switches for pneumatic applications. Extremely precise thanks to the large control diaphragm. Two through holes in the housing for flanging the switch.

Izstrādājums

Apzīmējums	iestatīšanas diapazons
-------------------	------------------------

K- 07 30 28 61	0,5 - 10,0 bar
-----------------------	----------------

ir piederums šādiem izstrādājumiem

K-VT SCHMAL MULTIFIX	Manifolds - narrow design
-----------------------------	---------------------------

K-VT BREIT MULTIFIX	Manifolds - wide design
----------------------------	-------------------------

ir rezerves daļa šādiem izstrādājumiem

K-VERTEILER HANSA	Manifolds
--------------------------	-----------