

# K-LKM S NW7,4 IG

Safety couplings DN 7.4, female

## Īpašības

<b>Ekspluatācijas spiediens</b>	Max. 12 bar, maximum static working pressure (non-pulsating)
<b>Iespējamo leņķu un nipeļu ekspluatācijas spiediens</b>	0 to 35 bar
<b>Gaisa caurplūde</b>	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Vielas temperatūra</b>	-20 °C to +60 °C
<b>Korpuss, vārsta korpuss</b>	Nickel-plated brass
<b>Vārsts</b>	Brass
<b>Atbloķēšanas uzdevs</b>	Plastic
<b>Atspere, sprostgredzens, tapas, lodes</b>	Stainless steel
<b>Bīvēšanas materiāls</b>	NBR



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

## Izstrādājums

Apzīmējums	Savienojums	Garums (mm)	SW (mm)
K- 07 35 03 01	G 1/4 female	57,2	22
K- 07 35 03 02	G 3/8 female	60,2	24
K- 07 35 03 03	G 1/2 female	60,2	24

## Papildedeļenti

<b>K-NIPPEL KUPPL NW7 AG VZ</b>	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
<b>K-NIPPEL KUPPL NW7 IG VZ 2</b>	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
<b>K-TUE 7,2 7,8 ST VZ 1</b>	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,