K-TR POLYURETHAN

Polyurethane hose (PUR)

HANSA FLEX

Īpašības

Darba spiediens	Max. 10 bar (at +20 °C)
Cietība	52 Shore D±3
Kalibrēšana	External
Vides temperatūra	-35 °C to +80 °C
Materiāls	Poliuretāns



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

This externally calibrated plastic hose made of high-quality polyester PUR is extremely flexible with optimal mechanical characteristics and very high pressure resistance across a wide temperature range. It is permanently flexible, boasts very good resilience and can be laid with a narrow bending radius. Its other advantages include good abrasion resistance, very good low-temperature flexibility and very high elongation at break. The hose is also suitable for vacuum applications. It is resistant to many different oils and lubricants (a special resistance test is recommended in specific cases owing to the additives that are blended in by the manufacturers), aliphatic hydrocarbons and gases such as oxygen, ozone, helium, etc.

Izstrādājums

Apzīmējums	Ø šļūtenei iekšpusē (mm)	Ø šļūtenei ārpusē (mm)	Liekuma rādiuss atkarīgs no caurplūdes (mm)	Krāsa	Ruļļa garums (m)
K- 07 10 05 47	2,6	4,0	17	Natural	25
K- 07 10 05 49	3,1	5,0	15	Natural	100
K- 07 10 05 48	3,1	5,0	15	zils	100
K- 07 10 05 51	9,0	12,0	67	Natural	100
K- 07 10 05 52	9,0	12,0	67	melns	100
K- 07 10 05 54	9,8	14,0	72	Natural	50
K- 07 10 05 53	9,8	14,0	72	zils	50
K- 07 10 05 55	9,8	14,0	72	melns	50
K- 07 10 05 56	11,0	16,0	88	Natural	50
K- 07 10 05 57	11,0	16,0	88	melns	50

Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.