


# K-ZFL ABSP-KLAPPEN EINFACH

Butterfly valves, with single-acting actuator - spring to close, min. pilot pressure 5 bar

**HANSA FLEX**

## Īpašības

<b>Modelis</b>	Pneumatic actuators, in double- or single acting version
<b>Ekspluatācijas spiediens</b>	Max. 16 bar
<b>Ekspluatācijas temperatūra</b>	-15 °C to +120 °C
<b>Darba vides</b>	Water / steam, salt water, salt water, ester, ketone, alkali, caustic soda, sodium hydroxide. Not recommended for hydrocarbons
<b>Regulēšanas spiediens</b>	5.5 bar
<b>Vārsta adapteris</b>	Supplied as standard, operated by a 3/2- or 5/2-way valve
<b>Griešanas leņķis</b>	90 °
<b>Piedziņa</b>	aluminium eloxed
<b>Piedziņas blīvējums</b>	NBR
<b>Korpuss</b>	Grey cast iron GG25 epoxy resin coated, RAL 5015
<b>Blīvējums</b>	EPDM
<b>Vārpsta</b>	SS416
<b>Vārpstas blīvējums</b>	EPDM
<b>Vadība</b>	



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Izstrādājums

Apzīmējums	Paplāksne	DN	B (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L (mm)
K- 07 30 03 36	Stainless Steel CF8M/1.4404	40	38,0	68,0	108,0	238,0	94,0
K- 07 30 03 37	Stainless Steel CF8M/1.4404	50	47,0	71,0	143,0	273,0	100,0
K- 07 30 03 38	Stainless Steel CF8M/1.4404	65	49,0	78,0	155,0	285,0	115,0
K- 07 30 03 39	Stainless Steel CF8M/1.4404	80	47,0	89,0	162,0	292,0	127,0
K- 07 30 03 40	Stainless Steel CF8M/1.4404	100	56,0	102,0	178,0	348,0	163,0
K- 07 30 03 42	Stainless Steel CF8M/1.4404	125	59,0	123,0	191,0	361,0	190,0
K- 07 30 03 44	Stainless Steel CF8M/1.4404	150	59,0	138,0	265,0	395,0	216,0