

# K-L-STECKVER ABSP DREH AG-K

Angle stop valves, swivel type, conical male thread, coated

**HANSA FLEX**

## Īpašības

|                        |  |
|------------------------|--|
| Darba spiediens        | Max. 10 bar, vacuum                      |
| Izmantošana            | Air, vacuum                              |
| Ieteicamās šļūtenes    | PU or PA (nylon)                         |
| Darba vides            | Saspiests gaiss                          |
| Standarts              | R thread acc. to ISO 7-1, thread coating |
| Temperatūras diapazons | 0 °C to +60 °C                           |
| Bļivēšanas virsma      | Conical version: thread coating          |
| Materiāls              | Plastic, Nickel plated brass             |
| Piespiedējgredzens     | Plastic                                  |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

The air supply is completely shut off as soon as the hose is disconnected from the union. The flow rate is only guaranteed if the hose is securely inserted.

## Izstrādājums

| Apzīmējums     | Vītnes | šļūtenes ārējam Ø | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|--------|-------------------|------------|------------|-------|
| K- 07 40 08 53 | R 1/8  | 4 mm              | 31,0       | 23,8       | 10 mm |
| K- 07 40 08 54 | R 1/8  | 6 mm              | 29,4       | 24,2       | 12 mm |
| K- 07 40 08 55 | R 1/8  | 8 mm              | 33,0       | 27,5       | 14 mm |
| K- 07 40 08 51 | R 1/4  | 6 mm              | 29,4       | 26,7       | 14 mm |
| K- 07 40 08 52 | R 1/4  | 8 mm              | 33,0       | 29,5       | 14 mm |
| K- 07 40 08 50 | R 1/4  | 10 mm             | 42,5       | 34,3       | 17 mm |
| K- 07 40 08 58 | R 3/8  | 8 mm              | 33,0       | 31,0       | 17 mm |
| K- 07 40 08 56 | R 3/8  | 10 mm             | 42,5       | 35,3       | 17 mm |
| K- 07 40 08 57 | R 3/8  | 12 mm             | 46,5       | 37,0       | 21 mm |
| K- 07 40 08 48 | R 1/2  | 10 mm             | 42,5       | 38,8       | 21 mm |
| K- 07 40 08 49 | R 1/2  | 12 mm             | 46,5       | 40,0       | 21 mm |